

Gigabit Switching with Fiber Expansion and Browser Configurability



This new Linksys rackmount switch delivers non-blocking, wire speed switching for your 10, 100, and 1000 megabit network clients, plus multiple options for connecting to your network backbone. Sixteen 10/100/1000 ports wire up your workstations, while the two mini GBIC ports allow future expansion to alternate transmission media like optical fiber for your backbone.

It features WebView monitoring and configuration via your web browser, making it easy to manage the 64 VLANs and up to 8 trunking groups. Or if you prefer, you can use the integrated console port to configure the switch. The non-blocking, wire-speed, full-duplex switching forwards packets as fast as your network can deliver them. Also included are Address Learning and Aging to prevent data transfer

errors and Data Flow Control to help prevent packet collisions. Four Quality of Service egress queues per port let you prioritize traffic via 802.1p. The switch provides broadcast storm suppression, has hardware MAC address learning, and supports packet filtering and port security.

All ports have automatic MDI/MDI-X crossover detection, so you don't have to worry about the cable type, and polarity detection will even automatically correct wiring errors. Each port independently and automatically negotiates for best speed and whether to run in half- or full-duplex mode. Head-of-line blocking prevention keeps your high-speed clients from bogging down in lower-speed traffic and fast store-and-forward switching prevents damaged packets from being passed on into the network.

No matter how intensive your network demands, the Linksys 16-Port 10/100/1000 Gigabit Switch with WebView has speed, flexibility, and reliability that you can count on.

16 autosensing
10/100/1000 full
duplex, auto
MDI/MDI-X ports

Two mini GBIC
expansion ports for
fiber expansion

WebView remote
monitoring and
configuration via
web browser

64 VLANs, 8 port
trunking groups,
console port, 802.1p
CoS support

16-Port 10/100/1000 Gigabit Switch with WebView



Product Data

Model No. **SRW2016**

16-Port 10/100/1000 Gigabit Switch with WebView

Features

- 16 10/100/1000 Gigabit Ethernet ports
- 2 MiniGBIC slots for Fiber and Copper Gigabit Ethernet expansion (Shared)
- Supports half duplex and full duplex modes and auto-negotiation for all 10/100/1000 Copper ports
- Auto MDI/MDI-X supports cable detection on all 10/100/1000 Copper ports
- Provides flow control mechanism to ensure zero packet loss. Uses backpressure for half-duplex operation and IEEE802.3x for full duplex operation.
- Supports 8K MAC address table entries.
- Supports 2Mbit packet memory.
- Supports Jumbo Frames sizes up to 9KB
- Provides Store-and-Forward switching mechanism.
- Provides non-blocking switching performance.
- Provides Multicasting, Broadcasting and Flooding Control.
- Four egress queues on all switch ports. Support for strict priority and weighted round-robin (WRR) CoS policies
- Traffic classification based on Port#, VLAN priority in VLAN tagging packet.
- Supports 802.1q Tagged based VLAN for support of up to 64 VLANs
- Supports up to 8 trunking groups.
- Load sharing among trunk ports based on MAC address.
- Port Mirroring to monitor the traffic of Mirrored ports.
- ACL to limit the interface and IP domain to manage the switch
- Web based configuration makes installation and setup easy

Specifications

Model	SRW2016 - 16-Port 10/100/1000 Gigabit Switch with WebView
Standards	IEEE 802.3, 802.3u, 802.3ab, 802.3x, 802.1p, 802.1q
Ports	16 10/100/1000 RJ-45 ports and 2 shared MiniGBIC slots
Cabling Type	Cat5e or better
LEDs	System, Link/Activity, Gigabits
Security Features	ACL, 802.1x

Environmental

Dimensions (W x H x D)	16.93" x 1.75" x 13.78" (430 mm x 44.45 mm x 350 mm)
Unit Weight	7.30 lbs. (3.31 kg)
Power Input	100-240V 0.5A
Certifications	UL (UL 1950), CSA (CSA 22.2), CE, EN60950 (2001)
Operating Temp.	0°C to 50°C (32°F to 122°F)
Storage Temp.	-40°C to 70°C (-40°F to 158°F)
Operating Humidity	20% to 95% Relative Humidity, Non-Condensing
Storage Humidity	5% to 90% Non-Condensing

Linksys
A Division of Cisco Systems, Inc.
18582 Teller Avenue
Irvine, CA 92612 USA

E-mail: sales@linksys.com
support@linksys.com

Web: <http://www.linksys.com>

Linksys products are available in more than 50 countries, supported by 12 Linksys Regional Offices throughout the world. For a complete list of local Linksys Sales and Technical Support contacts, visit our Worldwide Web Site at www.linksys.com.

Minimum Requirements

- Cat5 Ethernet Network Cable
- TCI/IP Protocol installed on each computer within the network
- Network Adapter installed in each computer
- Network Operating System (e.g. Windows®, Linux, MacOS X)

Package Contents

- SRW2016 - 16-Port 10/100/1000 Gigabit Switch with WebView
- AC Power Cord
- Rack Mounting Kit with brackets and hardware
- CD with User Guide in PDF format
- Warranty Card

Specifications are subject to change without notice. Linksys is a registered trademark or trademark of Cisco Systems, Inc. and/or its affiliates in the U.S. and certain other countries. Copyright © 2005 Cisco Systems, Inc. All rights reserved. Other brands and product names are trademarks or registered trademarks of their respective holders.