

C330MD

1/4" CCD Color Mini Dome Camera

Product Features

- 380 TV Lines resolution
- 2 Lux light sensitivity
- 3.6mm lens / F2.0
- Automatic electronic shutter
- Mounting hardware included
- 12 VDC
- Low power consumption
- Recommended power supply:
12VDC 300R



Specifications

TYPE	Color
SIGNAL FORMAT	PAL / NTSC
PICK UP DEVICE	1/4" CCD Image Sensor (Interline)
HORIZONTAL RES	380 Lines
MINI ILLUM	1.0 Lux F=2.0
ELECTRONIC SHUTTER	1/96,000 sec
C/N RATIO	46dB
SCANNING SYSTEM	2:1 Interlace
PICTURE ELEMENTS	EIA/NTSC: 512H x 492V - CCIR/PAL: 512H x 582V
HORIZ SYNC. FREQ	EIA/NTSC: 15.734 KHz - CCIR/PAL: 15.625 KHz
VERT. FREQ.	EIA/NTSC: 60Hz - CCIR/PAL: 50Hz
CLOCK FREQ.	NTSC: 28.636 Mhz PAL: 28.5 Mhz
VIDEO OUTPUT	1 V p-p, 75 Ohms
GAMMA	0.45
POWER SUPPLY	12 VDC (+/-0.5V)
POWER CONSUMPTION	110mA
DIMENSIONS HxD(mm)	52.5 x 87
WEIGHT	140g
FIXATION	3 screws
OPERATING TEMP	-10 to +45 C
STORAGE TEMP	-30 to +60 C

Specifications subject to change without notice.

2025 Opportunity Drive #1 Roseville, CA 95678
Toll free - (888) 771-4544 ● Phone - (916) 787-1100 ● Fax - (916) 787-1010
sales@armelectronics.com ● www.armelectronics.com

ARM
ELECTRONICS