

# TOSHIBA

# IK-6400A

DAY/NIGHT CCTV CAMERA



*The IK-6400A is the perfect choice where high resolution image quality is required in a 50dB, Day/Night camera*

- Day/Night Imaging Power – Color by Day and B&W at Night
- 10-Bit DSP Technology
- Advanced 1/3-inch Interlace CCD
- Low Light Sensitivity to 0.2Lux @F1.0
- Outstanding 50dB Signal-to-Noise Ratio
- Compact Dimensions Allow for Use with Smaller, Less Expensive Housings
- Razor-sharp 480 lines of Horizontal Resolution
- Backlight Compensation and Automatic Shutter
- Auto white Balance from 2,500°K to 10,000°K
- 3 Year Warranty



Lease This Product Call  
**800-207-8362**

# IK-6400A

## Day/Night CCTV Camera

<i>Pick-Up Element</i>	1/3" Interline Transfer CCD
<i>Effective Picture Elements</i>	771 (H) x 492 (V)
<i>Resolution</i>	480 TVL Horizontal
<i>Minimum Subject Illumination</i>	0.2 Lux @ F1.0
<i>AWB Range</i>	2,500°K to 10,000°K
<i>Lens Mount</i>	CS
<i>Backlight Compensation</i>	User Settable (On/Off)
<i>S/N Ratio</i>	50dB
<i>Video Output</i>	VBS 1V P-P (75 Ω)
<i>Video Format</i>	NTSC, 2:1 Interlace
<i>Sync System</i>	Line-Lock/Internal
<i>Line-Lock V-Phase Adjustment</i>	User Adjustable 0° - 300°
<i>Gamma Compensation</i>	0.45 fixed
<i>Shutter Control</i>	AES (1/60 to 1/100,000)
<i>AGC</i>	18dB
<i>Ambient Temperature</i>	14°F to 122°F (-10°C to +50°C)
<i>Camera Mounting Method</i>	1/4-inch x 20 Threaded Hole Provided (Top and Bottom)
<i>Power Supply</i>	AC 24V ±10%/60Hz ±1Hz DC 12V±10%
<i>Dimensions (inches)</i>	2.46(W) x 1.97(H) x 4.57(D)
<i>Weight</i>	12.3 ounces
<i>Auto-Iris Lens Support</i>	DC/Video, 4 Pin Connector
<i>Day/Night Function</i>	Yes
<i>Safety Standard</i>	UL2044, CSA
<i>Emission Standard</i>	FCC class A, DOC Class A

Specifications subject to change without notice

## New From Toshiba



**IK-WB02A**  
PoE Network Camera



**EVR**  
Fault Tolerant DVR



**IK-DP20A**  
Day/Night PTZ Dome



**IK-65WDA**  
Wide Dynamic Color Camera

